



# MPG RED GUARD

## Multi-Purpose High Temp Grease



**Description:** A multi-use grease for hundreds of automotive, marine, and agricultural applications. Extreme pressure additives give resistance to shock impact. Bentone based formula does not liquefy at high temperatures like soap based greases, yet remains pumpable at low temperatures. Forms a protective film, resists rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out even by boiling water and steam.

**Directions:** Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

**Benefits-Features:** HIGH SHOCK AND IMPACT RESISTANCE • TEMPERATURE RESISTANT FROM 0° TO 600°F • RESISTS ACIDS, WATER, SALT SPRAY, DUST, AND DIRT • BENTONE BASED FORMULA

**Advantages:** ALL WEATHER PERFORMANCE • UNIQUE RUST & CORROSION INHIBITORS • EXTREME PRESSURE ADDITIVES FOR HIGH LOADS • WILL NOT WASH OUT, EVEN WITH BOILING WATER OR STEAM

**Where to Use:** OVENS • DRYERS • GEARS • VALVES • PUMPS • WINCHES • CONVEYORS • CHAIN DRIVES • FITTINGS • LINKAGES • WIRE ROPE • HOISTS • THREADS • ROLLERS • CAMS • SLIDE BEARINGS • O-RINGS • MANIFOLD HEAT VALVES

**Recommended For:** DAIRIES • FREEZE DRYING OPERATIONS • HOT AIR DRYING OPERATIONS • BAKERIES • MARINAS • SHIPPING • AIR-CRAFT MAINTENANCE • PACKAGING & MOLDING OPERATIONS • SHIPPING OPERATIONS



**ISSA** The Experts  
on Cleaning and Maintenance  
MEMBER